

UNITED STATES PATENT APPLICATION FOR


EXPOSURE CONTROL IN  
A DIGITAL CAMERA

Inventor:  
Richard L. Baer

CERTIFICATE OF MAILING BY "EXPRESS MAIL"  
UNDER 37 C.F.R. § 1.10

"Express Mail" mailing label number: EI560987430US  
Date of Mailing: 4-25-2001

I hereby certify that this correspondence is being deposited with the United States Postal Service, utilizing the "Express Mail Post Office to Addressee" service addressed to **Assistant Commissioner for Patents, Washington, D.C. 20231** and mailed on the above Date of Mailing with the above "Express Mail" mailing label number.

  
\_\_\_\_\_  
Paul H. Horstmann, Reg. No. 36,167  
Signature Date: 4-25-2001

09342549.042501

BACKGROUND OF THE INVENTION

Field of Invention

5 The present invention pertains to the field of exposure control in cameras. More particularly, this invention relates to exposure control in a digital camera.

Art Background

10 Cameras including digital still cameras and video cameras typically include an image sensor and an exposure mechanism for controlling the amount of light from an image scene that reaches the image sensor. Digital cameras, for example, usually  
15 include a charge-coupled device (CCD) array as an image sensor along with mechanisms that control aperture and shutter speed exposure settings.

20 Image scenes often include objects which are very bright in comparison to other objects. For example, light sources such as light bulbs, candles, etc., in a relatively dark image scene are usually very bright in comparison to the remainder of the image scene. In addition, direct reflections of  
25 light sources from highly reflective surfaces in an image scene are usually very bright in comparison to the remainder of the image scene.

30 Exposure control in a camera typically involves determining the exposure settings that best utilize the dynamic range of the image sensor given the characteristics of an image scene being photographed. The dynamic range of an image sensor may be defined as the ratio of its highest possible signal output to

its lowest useful signal output. In a CCD array, for example, the highest possible signal output is usually limited by its charge capacity and its lowest useful signal output is usually limited by circuit noise.

5

Prior methods for exposure control in a camera typically involve measuring the average intensity of light from a sample area of an image scene being photographed and then selecting exposure settings that scale that average to a predetermined percentage of the dynamic range of the image sensor. However, light sources and reflections of light sources in the sample area usually yield a relatively high average intensity. A relatively high average intensity typically results in relatively low exposure settings using prior methods. Such low exposure settings typically reduce the intensity of light obtained from areas of the image scene outside of the light sources and reflections of light sources to the low end of the dynamic range of the image sensor. Unfortunately, this typically causes areas of interest in the image scene to appear too dark once photographed.

10

15

20

09642549 042501  
105240 6452490

SUMMARY OF THE INVENTION

5 A method for exposure control is disclosed which yields exposure settings just high enough to clip light sources and reflections of light sources in an image scene while allocating the majority of image sensor dynamic range to the remaining objects in the image scene. Exposure control according to the present techniques includes determining a number of  
10 clipped pixels from an image scene for one or more of a set of possible exposures and determining a selected exposure from the possible exposures such that the possible exposures higher than the selected exposure increase the number and the possible  
15 exposures less than the selected exposure do not substantially decrease the number.

20 The present techniques yield exposure settings that prevent light sources and reflections from light sources from causing an under exposure of the areas of primary interest in an image scene. Instead, the dynamic range of an image sensor is used to sample the areas of primary interest.

25 Other features and advantages of the present invention will be apparent from the detailed description that follows.

**BRIEF DESCRIPTION OF THE DRAWINGS**

The present invention is described with respect to particular exemplary embodiments thereof and  
5 reference is accordingly made to the drawings in which:

**Figure 1** shows a method for exposure control according to the present teachings;

10

**Figure 2** shows a camera which incorporates the present teachings;

**Figure 3** shows an example image scene for which  
15 an image processor determines an exposure using the present techniques;

**Figure 4** is a graph that illustrates the determination of the number of clipped pixels in an  
20 image scene;

**Figure 5** is a graph that illustrates the determination of a selected exposure from the possible exposures.

105240" 64524350

DETAILED DESCRIPTION

5     **Figure 1** shows a method for exposure control according to the present teachings. The method shown may be used for exposure control in a still camera or a video camera.

10     At step 100, a number of clipped pixels ( $P_c$ ) from an image scene being photographed is determined for each of a set of possible exposures. The arrangement of possible exposures depends on the exposure mechanism in the camera. For example, a camera may provide an aperture mechanism having a set of possible f-stops and a shutter mechanism having a set of possible shutter speeds. The number of clipped pixels at a given exposure depends on the image scene and the dynamic range of the image sensor in the camera.

20     Step 100 may be performed by photographing an image scene of interest for each possible combination of aperture and shutter speed settings. A starting exposure may be selected and then varied while gathering data on the number of clipped pixels. Step 25 100 may be performed for the entire image scene being photographed or for a sub-portion of the image scene being photographed.

30     At step 102, a selected exposure is determined from the possible exposures such that the possible exposures higher than the selected exposure increase the number  $P_c$  and the possible exposures less than the selected exposure do not increase the number  $P_c$ . This

09842549-042501

10 yields a selected exposure which clips light sources  
and reflections of light sources in the image scene  
and which allocates the majority of the dynamic range  
of the image sensor to measure light from the  
5 remainder of the image scene outside of the light  
sources and reflections of light sources.

**Figure 2** shows a camera 10 which incorporates  
the present teachings. The camera 10 includes a lens  
10 mechanism 12 that conducts light from an image scene  
through an aperture mechanism 14 and a shutter  
mechanism 16 to an image sensor 18. An image  
processor 22 controls the aperture mechanism 14 and  
the shutter mechanism 16 via a set of control signals  
15 24.

In one embodiment, the image sensor 18 includes  
an array of CCD sensors. Each sensor in the array is  
referred to as a pixel and an image scene sampled by  
20 the image sensor 18 is treated as an array of pixel  
samples. In response to light from an image scene  
received via the lens mechanism 12, the aperture  
mechanism 14, and the shutter mechanism 16, the image  
sensor 18 generates a set of pixel samples and  
25 provides the pixel samples to an analog-to-digital  
(A/D) converter 20. The A/D converter 20 digitizes  
the pixel samples and provides the corresponding  
digitized pixel samples to the image processor 22.  
Each digitized pixel sample is a digital value that  
30 indicates a charge amplitude from the corresponding  
sensing element of the image sensor 18.

5 The image processor 22 obtains digitized pixel samples from the A/D converter 20 and performs the present techniques for exposure control. The image processor 22 adjusts the aperture mechanism 14 and the shutter mechanism 16 and analyzes the resulting digitized pixel samples to perform step 100. The image processor 22 uses the data gathered at step 100 to determine a selected exposure at step 102 and then sets the selected exposure using the aperture mechanism 14 and the shutter mechanism 16.

15 In one embodiment, the camera 10 is a still image camera. In another embodiment, the camera 10 is a video camera. The image processor 22 including exposure control functionality may be implemented in hardware and/or software or firmware. The aperture mechanism 14 and the shutter mechanism 16 may be any known mechanisms useful in cameras.

20 **Figure 3** shows an example image scene 30 for which the image processor 22 in the camera 10 determines an exposure using the present techniques. The image scene 30 includes a light source 36 and a set of reflecting areas 32-34 which are reflections from the light source 36.

30 **Figure 4** is a graph 200 that illustrates the determination of the number of clipped pixels in the image scene 30 at step 100. The graph 200 is a histogram for a given exposure setting of the camera 10. The histogram shows the number of digitized pixel samples from the image scene 30 at each possible pixel amplitude.



5

10

20

25

average amplitude of digitized pixel samples from the  
image scene 30 or sub area of the image scene 30 and  
then setting the starting exposure so that the  
average is a predetermined percentage of the dynamic  
5 range of the image sensor 18.

10 A region 222 of the graph 220 represents a range  
in which the number of clipped pixels is not a strong  
function of the exposure. In the region 222, the  
graph 220 is relatively flat and the number of  
clipped pixels is relatively unchanged as the  
exposure changes. A point 224 of the graph 220 is an  
15 exposure at which the number of clipped pixels begins  
to increase as the exposure increases. The image  
processor 22 detects the point 224 at step 102 and  
uses the corresponding exposure as the selected  
exposure for photographing the image scene 30.

20 The increase in the number of clipped pixels at  
point 224 indicates that bright pixels in the image  
scene 30 outside of the light source 36 and the  
reflecting areas 32-34 are beginning to be clipped.  
An exposure setting at point 224 will clip the light  
source 36 and the reflecting areas 32-34 as is  
25 desired and will scale the remaining brightest pixels  
in the image scene 30 to the top of the dynamic range  
of the image sensor 18. The lower dynamic range of  
the image sensor 18 is then available to accurately  
measure the darker pixels in the image scene 30.

30

In one embodiment, the camera 10 includes a  
button that controls when image samples are obtained.  
The image processor 22 performs the present

techniques for exposure control upon first actuation of the button and then obtains image samples on the next actuation of the button using the selected exposure.

5

The foregoing detailed description of the present invention is provided for the purposes of illustration and is not intended to be exhaustive or to limit the invention to the precise embodiment disclosed. Accordingly, the scope of the present invention is defined by the appended claims.

10

09842549-042501